

**PETROTHENE® NA963083**

**SECTION 1: IDENTIFICATION**

**Product Name:** PETROTHENE® NA963083

**Product Number:** 000000000000504614

**Internal ID:** P177

**Chemical Family:** Polyethylene Homopolymer

**CAS Number:** 9002-88-4

**Chemical Name:** Polyethylene Homopolymer

**Synonyms:** Polyethylene, Polyethylene Homopolymer, PE

**Company**

Equistar Chemicals, LP  
One Houston Center, Suite 700  
1221 McKinney St.  
P.O. Box 2583  
Houston Texas 77252-2583

**Business Contact**

Customer Service  
888 777-0232  
Product Safety  
800 700-0946  
product.safety@lyondell.com

**24 Hour Emergency Contact**

CHEMTREC 800 424-9300  
EQUISTAR 800-245-4532

**SECTION 2: HAZARD IDENTIFICATION**

**Emergency Overview**

This material is NOT HAZARDOUS by OSHA Hazard Communication definition. Trade secret chemical identities will be revealed to treating physicians in an emergency, or to purchasers after execution of a secrecy agreement.


**Signal Word**

CAUTION.

**Hazards**

Dust may form explosive mixtures with air. At process temperatures irritating fumes may be produced. Molten polymer may cause thermal burns.

NFPA®



HMIS®

|                 |   |
|-----------------|---|
| Health          | 1 |
| Flammability    | 1 |
| Physical Hazard | 0 |

**Physical State**

Solid

**Color**

Translucent to white.

**PETROTHENE® NA963083****Odor**

Faint, mild hydrocarbon odor.

**Odor Threshold**

No value available.

**Potential Health Effects****Routes of Exposure**

Eye. Inhalation. Skin.

**Signs and Symptoms of Acute Exposure**

See component summary.

- *Polyethylene, Homopolymer 9002-88-4*

Hot material may cause thermal burns. At process temperatures, irritating fumes may cause soreness in the nose and throat; coughing may result. Mechanical irritation is possible.

- *Proprietary Additive Mixture*

No known acute health effects.

**Skin**

Molten polymer may cause thermal burns.

**Inhalation**

Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. "Nuisance dust" such as polymer dust typically exhibit no significant health effect when they are reasonably controlled. Exposure to high concentrations of dust may cause slight irritation by mechanical action.

**Eye**

Mechanical irritation is possible.

**Ingestion**

Ingestion not a likely route of exposure.

**Chronic Health Effects**

See component summary.

- *Polyethylene, Homopolymer 9002-88-4*

No known chronic health effects.

- *Proprietary Additive Mixture*

No known chronic health effects.

**Conditions Aggravated by Exposure**

No known conditions are aggravated by this material.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

| <u>Component Name</u>     | <u>CAS #</u> | <u>EU Inventory</u>            | <u>Concentration Wt. %</u> |
|---------------------------|--------------|--------------------------------|----------------------------|
| Polyethylene, Homopolymer | 9002-88-4    | Monomers are<br>EINECS listed  | 98.0 <= 100.0              |
| Proprietary Additive      | Mixture      | Additives are<br>EINECS listed | <= 2.0                     |

## **PETROTHENE® NA963083**

Compositions given are typical values not specifications.

### **SECTION 4: FIRST AID MEASURES**

---

#### **General**

Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. For specific information refer to the Emergency Overview in Section 2 of this MSDS.

#### **Skin**

If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin. Obtain immediate emergency medical attention if burn is deep or extensive.

#### **Inhalation**

If symptoms are experienced, move victim to fresh air. Obtain medical attention if breathing difficulty persists.

#### **Eye**

Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists.

#### **Ingestion**

Adverse health effects due to ingestion are not anticipated.

### **SECTION 5: FIRE FIGHTING MEASURES**

---

#### **Flammable Properties**

##### **Classification**

Not Classified. Polymer will burn but does not easily ignite.

##### **Flash Point**

Not applicable.

##### **Auto-Ignition Temperature**

343 °C (649.4 °F)

##### **Lower Flammable Limit**

Not applicable.

##### **Upper Flammable Limit**

Not applicable.

#### **Extinguishing Media**

##### **Suitable:**

SMALL FIRE: Use DRY chemicals, CO<sub>2</sub>, water spray LARGE FIRES: Use large quantities of water spray.

#### **Protection of Firefighters**

##### **Protective Equipment/Clothing:**

Wear an approved positive pressure self-contained breathing apparatus and firefighter turnout gear.

##### **Fire Fighting Guidance:**

Polyolefin dust particles in the atmosphere are combustible and may be explosive. Keep away from heat, sparks, open flame, or any ignition source.

## **PETROTHENE® NA963083**

### **Hazardous Combustion Products:**

Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

---

### **Release Response**

Equip responders with proper protection. Potential dust explosion hazard. Avoid generating dust. Creates dangerous slipping hazard on any hard smooth surface. With clean shovel place material into clean, dry container and cover loosely; move containers from spill area. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.

## **SECTION 7: HANDLING AND STORAGE**

---

### **Handling**

Keep material off walking surfaces, it may create a slipping hazard. Polymer dust may form explosive mixtures with air. Avoid accumulation of dust in enclosed space. Use in well-ventilated area. Ground and bond equipment to prevent electrostatic charge when transferring product. Control spilled material to prevent runoff to the sewers and the environment. After handling, always wash hands thoroughly with soap and water.

### **Storage**

Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination.

## **SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION**

---

### **Engineering Controls**

Ventillate area to prevent accumulation of dust and fumes.

### **Personal Protection**

#### Inhalation

A respiratory protection program that meets OSHA's 29 CFR 1910.134 or ANSI Z88.2 requirements must be followed whenever workplace conditions warrant respirator use. Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. Use appropriate respiratory protection where atmosphere exceeds recommended limits.

#### Skin

Wear heat protective gloves and clothing if there is a potential for contact with heated material. Wear heat protective gloves and clothing if there is a potential for contact with heated material. Protective clothing such as long sleeves or a lab coat should be worn.

#### Eye

Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due to airborne particles which may result from handling this product.

### **Additional Remarks**

Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/wash thoroughly before reuse. Material spilled on hard surface can be a serious slipping/falling hazard. Use care in walking on spilled material.

## **PETROTHENE® NA963083**

### **Occupational Exposure Limits**

Consult local authorities for acceptable exposure limits.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

---

**Appearance:** Solid Translucent to white.

**Odor:** Faint, mild hydrocarbon odor.

**Odor Threshold:** No value available.

**pH:** Not applicable.

**Boiling Point/Boiling Range:** Not applicable.

**Freezing Point/Melting Point:** 104 - 138 °C (219.2 - 280.4 °F)

**Flash Point:** Not applicable.

**Auto-ignition:** 343 °C (649.4 °F)

**Flammability:** Not Classified. Polymer will burn but does not easily ignite.

**Lower Flammable Limit:** Not applicable.

**Upper Flammable Limit:** Not applicable.

**Explosive Properties:** No Data Available.

**Oxidizing Properties:** No Data Available.

**Vapor Pressure:** Not applicable.

**Evaporation Rate:** Not applicable.

**Relative Density:** ~ 0.91 - 0.98

**Relative Vapor Density:** Not applicable.

**Viscosity:** Not applicable.

**Solubility (Water):** Insoluble.

**Partition Coefficient (Kow):** Specific data not available.

**Additional Physical and Chemical Properties:** No additional information available.

### **SECTION 10: STABILITY AND REACTIVITY**

---

#### **Chemical Stability**

The product is stable.

## **PETROTHENE® NA963083**

### **Conditions to Avoid**

Avoid contact with strong oxidizers, excessive heat, sparks or open flame.

### **Substances to Avoid**

Material may be softened by some hydrocarbons.

### **Decomposition Products**

Not expected to decompose under normal conditions.

### **Hazardous Polymerization**

Will not occur.

### **Reactions with Air and Water**

Does not react with air, water or other common materials.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

---

### **PRODUCT INFORMATION**

#### **Product Summary**

See components summary.

### **COMPONENT INFORMATION**

---

- *Polyethylene, Homopolymer 9002-88-4*

#### **Acute Toxicity - Effects**

##### Inhalation

Rats inhaling polyethylene dust developed mild inflammatory changes in the lungs.

##### Ingestion

No adverse health effects were noted on the digestive system of test animals when fed up to 20% polyethylene.

#### **Repeated Dose Toxicity**

Subchronic, 50-90 day, feeding studies conducted on rats, dogs and swine showed no effects from dietary levels of 1-20% powdered and shredded polyethylene.

#### **Reproductive Effects**

Not expected to occur.

#### **Carcinogenicity**

Not listed by IARC, NTP, OSHA or EPA.

- *Proprietary Additive Mixture*

#### **Repeated Dose Toxicity**

No known chronic health effects.

#### **Carcinogenicity**

Not listed by IARC, NTP, OSHA or EPA.

## **SECTION 12: ECOLOGICAL INFORMATION**

---

## **PETROTHENE® NA963083**

### **PRODUCT INFORMATION**

---

#### **Ecotoxicity**

See components summary.

#### **Environmental Fate and Pathway**

See components summary.

### **COMPONENT INFORMATION**

---

- *Polyethylene, Homopolymer 9002-88-4*

#### **Ecotoxicity**

Ecotoxicity is expected to be minimal based on the low water solubility of polymers.

#### **Environmental Fate and Pathway**

This material is not volatile and insoluble in water.

##### Persistence and Degradability

Biodegradation: This material is not expected to be readily biodegradable.

Bioaccumulation: This material is not expected to bioaccumulate.

- *Proprietary Additive Mixture*

#### **Ecotoxicity**

No Data Available.

#### **Environmental Fate and Pathway**

No Data Available.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

---

All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Use only licensed transporters and permitted facilities for waste disposal.

### **SECTION 14: TRANSPORT INFORMATION**

---

#### **Special Requirements**

If you reformulate or further process this material, you should consider re-evaluation of the regulatory status of the components listed in the composition section of this sheet, based on final composition of your product.

**PETROTHENE® NA963083****Proper Shipping Name** POLYETHYLENE, OTHER THAN LIQUID, NOT REGULATED**SECTION 15: REGULATORY INFORMATION**

---

**Regulatory Status**

| Country        | Inventory |
|----------------|-----------|
| Australia      | AICS      |
| Canada         | DSL       |
| China          | IECS      |
| European Union | EINECS    |
| Japan          | ENCS      |
| Korea          | ECL       |
| Philippines    | PICCS     |
| United States  | TSCA      |

Contact Product.Safety@Lyondell.com for additional global inventory information.

If identified components of this product are listed under the TSCA 12(b) Export Notification rule, they will be listed below.

**SARA 302/304**

This product contains no known chemicals regulated under SARA 302/304.

**SARA 311/312**

Based upon available information, this material is not classified as a health and/or physical hazard according to Section 311 & 312.

**SARA 313**

This product contains no known chemicals regulated under SARA 313.

**State Reporting**

This product contains no known chemicals regulated by California's Proposition 65.

This product contains no known chemicals regulated by New Jersey's Worker and Community Right to Know Act.

This product contains no known chemicals regulated by Massachusetts' Right to Know Law.

This product contains no known chemicals regulated by Pennsylvania's Right to Know Act.

**SECTION 16: OTHER INFORMATION**

---

**Latest Revision(s)**

Reviewed Revised Section(s): 14 February 2008

---

**DISCLAIMER OF RESPONSIBILITY**

CAUTION DO NOT USE EQUISTAR MATERIALS IN APPLICATIONS INVOLVING IMPLANTATION WITHIN THE



## **PETROTHENE® NA963083**

---

### **DISCLAIMER OF RESPONSIBILITY**

BODY; DIRECT OR INDIRECT CONTACT WITH THE BLOOD PATHWAY; CONTACT WITH BONE, TISSUE, TISSUE FLUID, OR BLOOD; OR PROLONGED CONTACT WITH MUCOUS MEMBRANES. EQUISTAR MATERIALS ARE NOT DESIGNED OR MANUFACTURED FOR USE IN IMPLANTATION IN THE HUMAN BODY OR IN CONTACT WITH INTERNAL BODY FLUIDS OR TISSUES. EQUISTAR WILL NOT PROVIDE TO CUSTOMERS MAKING DEVICES FOR SUCH APPLICATIONS ANY NOTICE, CERTIFICATION OR INFORMATION NECESSARY FOR SUCH MEDICAL DEVICE USE REQUIRED BY FDA REGULATION OR ANY OTHER STATUTE. EQUISTAR MAKES NO REPRESENTATION, PROMISE, EXPRESS WARRANTY OR IMPLIED WARRANTY CONCERNING THE SUITABILITY OF THESE MATERIALS FOR USE IN IMPLANTATION IN THE HUMAN BODY OR IN CONTACT WITH INTERNAL BODY TISSUES OR FLUIDS. The information on this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this MSDS information may not be applicable.

#### Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg

#### Language Translations

This document may be available in languages other than English.

< end of document >